



Product Specification Sheet

Series Cement Test Chambers

Model ecmt-1620

1620 litre cement test chamber







Product Specification Sheet

Series Cement Test Chambers Model ecmt-1620

1620 litre cement test chambe

Chamber capacity 1620 Litres

Standard dual chamber design 1 set of shelves per door

Chamber width 705 mm
Chamber depth 600 mm
Chamber height 1810 mm

Single chamber design Optional
Chamber width 1490 mm
Chamber depth 600 mm
Chamber height 1810 mm

Chamber material Stainless Steel 304L

External width 1895 mm
External depth 762 mm
External height 2401 mm

External material Durable epoxy powder-coated steel

Recommended clearance 75mm on sides and rear

Temperature sensor Pt100
Control accuracy 0.1 C
Temporal stability 0.2 C

Humidity sensor

Control accuracy 0.1 % Temporal stability 0.5 %

Designed for optimum performance at:

23C 50% RH23C 90% RH23C 95%RH

Compliant with AS2350.13 - 2006

AS5101.4 - 2008

Steridium Pty Ltd | Brisbane | Australia | www.steridium.com | sales@steridium.com | +61 7 55 931 352





Product Specification Sheet

Series Model **Cement Test Chambers**

Model ecmt-1620

1620 litre cement test chamber

Available shelf positions 38 (19 per door)
Shelves supplied 8 (4 per door)
Shelf dimensions 690 x 590 mm

Shelf spacing 90 mm

Shelf capacity 100 KG—reinforced shelves

Insulation type Mineral Wool - asbestos free

Insulation thickness 50mm

Compressor size 3/4 HP

Refrigerant CFC-Free R134a

Electrical supply Single phase, 220 - 240V, 50 - 60 Hz

(alternatives available on request)

Water supply Potable

Water filter Onboard - three stage

Element rating 2 kW

Circulating fan 2

Countdown timer 99 hr 59 min - or continuous

Controller type Multifunction intelligent digital PID-microprocessor
Readout Digital LCD readout of set and actual temperature

Temperature alarms High | low | deviation

Country of origin Australia

Steridium Pty Ltd | Brisbane | Australia | www.steridium.com | sales@steridium.com | +61 7 55 931 352





Product Specification Sheet

Series Cement Test Chambers

Model ecmt-1620

1620 litre cement test chamber

Options / Accessories

- Single chamber design
- Additional shelves
- Inner viewing door toughened glass
- · Double glazed glass door
- Side access port 50 mm
- Internal power supply
- Inner viewing light LED
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate
- Water tank (where no water supply available)

Steridium Pty Ltd | Brisbane | Australia | www.steridium.com | sales@steridium.com | +61 7 55 931 352